

RESPONSE TO OFFICE ACTION  
Serial No. 10/648,729  
Page 2 of 14

**IN THE CLAIMS:**

1. (Currently Amended) A filter assembly comprising:  
a frame assembly;  
a filter media pack disposed in the frame assembly;  
a first compressible seal element disposed on a first side of an edge of the media pack and engaged with the frame assembly; and  
a second seal element disposed on a second side of the edge of the media pack and engaged with the frame assembly, the second seal member biasing the edge of the media pack against the first seal element.
2. (Original) The filter assembly of claim 1, wherein the media pack is pleated.
3. (Currently Amended) The filter assembly of claim 2, wherein the first and second seal elements compress a pleat pleated edge of the filter media pack.
4. (Original) The filter assembly of claim 1, wherein the first seal element has a serrated edge disposed against the filter media pack.
5. (Currently Amended) The filter assembly of claim 1, wherein the ~~first~~ second seal element is compressible.
6. (Original) The filter assembly of claim 1, wherein the first seal element is a plastic.
7. (Original) The filter assembly of claim 1, wherein the first seal element is a foamed plastic.
8. (Original) The filter assembly of claim 1, wherein the first seal element is an elastomer.

369391

**RESPONSE TO OFFICE ACTION**  
**Serial No. 10/648,729**  
**Page 3 of 14**

9. (Original) The filter assembly of claim 1, wherein the first seal element further comprises:

an edge disposed against the filter media pack; and  
at least one seal feature disposed on the edge.

10. (Original) The filter assembly of claim 8, wherein the seal feature further comprises:

a rib extending from the edge.

11. (Original) The filter assembly of claim 8, wherein the seal feature further comprises:

a groove formed in the edge.

12. (Original) The filter assembly of claim 1 further comprising:

third and fourth seal elements clamping an edge of the filter media pack opposite an edge clamped by the first and second seal elements.

13. (Original) The filter assembly of claim 12 further comprising:

an adhesive sealing an edge of the media pack adjacent the edge of the media pack proximate the first seal element.

14. (Original) The filter assembly of claim 13, wherein the adhesive is selected from the group consisting of at least one of epoxy, tape, urethane, acrylic, latex and potting material.

15. (Currently Amended) The filter assembly of claim 12 further comprising:

a high loft material disposed between an edge of the media pack adjacent the edge of the media pack proximate the first seal element and the housing frame assembly.

**RESPONSE TO OFFICE ACTION**  
**Serial No. 10/648,729**  
**Page 4 of 14**

16. (Currently Amended) The filter assembly of claim 1, wherein the frame assembly ~~bases~~ biases the first and second seal elements toward one another.

17. (Currently Amended) The filter assembly of claim 1, wherein the frame assembly further comprises:

an upstream portion; and

a downstream portion coupled to the upstream portion thereby sandwiching the first seal element, the second seal element and the media pack therebetween.

18. (Original) The filter assembly of claim 1, wherein the first seal element is biased against the media pack in a direction parallel to an air flow direction through the media pack.

19. (Original) The filter assembly of claim 1, wherein at least one of the seal elements is biased against a side of the frame assembly.

20. (Original) The filter assembly of claim 1 further comprising:  
a grille disposed alongside the media pack.

21. (Currently Amended) A filter assembly comprising:  
a frame assembly having sides defining an opening through the frame assembly, each side having at least one inwardly extending flange;  
a filter media pack disposed in the opening frame assembly and having opposing first and second open ends and opposing first and second closed ends;  
a first pair of seal elements disposed in the frame assembly and clamping the first open end of the media pack; and  
a second pair of seal elements disposed in the frame assembly and clamping the second open end of the media pack, wherein at least one of the first pair of seal elements and at least one of the second pair of seal elements are compressible.

369391

**RESPONSE TO OFFICE ACTION**  
Serial No. 10/648,729  
Page 5 of 14

22. (Currently Amended) A method of fabricating a filter, comprising:  
placing a filter media pack in at least a first portion of a housing assembly;  
and  
compressing an edge of the filter media pack between a first and second seal member, wherein at least one of the first or second seal members is compressible.
23. (Original) The method of claim 22, wherein the step of compressing further comprises:  
joining a second portion of the housing to the first portion of the housing, wherein the housing urges the first and second seal members toward each other.
24. (Currently Amended) The method of claim 22 further comprising:  
placing the first seal member in the housing with a serrated edge facing inward.
25. (Currently Amended) The method of claim 24, wherein the first seal member is placed in the housing before the media pack.
26. (Currently Amended) The method of claim 24, wherein the first seal member is placed in the housing after the media pack.
27. (Currently Amended) The method of claim 22, wherein the second seal member is inserted into the housing after the housing assembly is assembled around the media pack.

RESPONSE TO OFFICE ACTION  
Serial No. 10/648,729  
Page 6 of 14

28. (Currently Amended) A filter assembly fabricated by the process comprising:

inserting a pleated filter media pack into a filter frame;

inserting a first seal member into the filter frame proximate a first open edge of the filter media pack;

clamping a first open edge of a pleated filter media pack between a the first open edge of the filter media pack between the first seal member and a second compressible seal member; and

clamping a second open edge of the pleated filter media pack between a third and fourth seal member.

369391